



Product Catalog



About Tatko Tires

With a history approaching a century, we have been the foremost observer of the Turkish tire industry for 96 years. Our mark on the sector dates back to our establishment in 1927. We take pride in our 600 dedicated employees, our diverse range of products, our partnerships with world-leading brands, and our very own brand, Tatko.

As Turkey's largest multi-brand retail tire chain, we continue to serve our customers with an extensive product portfolio through our network of 800 dealers. We stand by our customers by offering comprehensive 360° service packages comprising tire supply, uninterrupted operational support, our digital fleet solution software and retreading services, all of which constitute our Commercial Tires and Off-Road operations.

Thanks to our efficient logistics operations, we ensure a seamless tire supply to our customers through our Central Tire Base and warehouses spread across the country. Furthermore, our commitment to sustainability and environmentally friendly practices has enabled us to reuse "70 million kg of tires (70 thousand tons)" in the last 30 years, achieved through Turkey's largest retreading facilities.

Drawing on our extensive 360-degree experience in the tire industry, we branched out to introduce our own brand. Tatko brand has gained recognition in nearly 40 countries across 5 continents, spanning from Europe to Asia, North America to Africa. Tatko products conform to international standards such as DOT, ECE, INMETRO, and hold certifications such as ISO 9001, ISO 14001, ISO 45001, and ISO 27001.

In our second century, we will continue to leave our mark by adding value to our employees and business partners.



Agro Tire Family



Power X

Farm-R

Farm-F

Flot-141

IMP-111

RMK-121

RMK-131

Industrial Tire Family



SK-165

CST-27

Off-The- Road Tires



Hi-Traction
Grader



AGRO

AGRO



POWER-X

Radial Tractor Tire

- ✔ The deep treads and wide footprint allow for superior performance
- ✔ The flexible sidewall structure ensures a safe and comfortable driving experience
- ✔ Its tread pattern and void area design incorporate mud-repelling features

TATKO



POWER-X

Radial Tractor Tire



Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
70 SERIES												
UR7016240102TAT	240/70 R16	TL	9,6	29,3	104/104	A8/B	32	R-1W	1980	34	88	13,3
UR7016240102TAT	260/70 R16	TL	10,2	30,3	109/109	A8/B	33	R-1W	2270	34	90,7	13,7
UR7016240102TAT	280/70 R16 (7.50 R16)	TL	11,1	31,4	112/112	A8/B	35	R-1W	2470	34	93,9	14,2
UR7016240102TAT	280/70 R18 (7.50 R18)	TL	11,1	33,4	114/114	A8/B	35	R-1W	2600	34	100,2	15,2
UR7016240102TAT	260/70 R20	TL	10,2	34,4	113/113	A8/B	34	R-1W	2540	34	103,7	15,8
UR7016240102TAT	280/70 R20 (7.50 R20)	TL	11,1	35,4	116/116	A8/B	38	R-1W	2760	34	106,5	16,2
UR7016240102TAT	300/70 R20 (9.50 R20)	TL	11,6	37,5	120/117	A8/B	38	R-1W	3080	34	112,2	17
UR7016240102TAT	320/70 R24 (11.2 R24)	TL	12,6	43,1	116/116	A8/B	43	R-1W	2760	23	129,4	19,6
UR7016240102TAT	360/70 R24 (12.4 R24)	TL	14	45,4	122/122	A8/B	47	R-1W	3300	23	135,8	20,6
UR7016240102TAT	380/70 R24 (13.6 R24)	TL	14,5	46,6	125/125	A8/B	53	R-1W	3640	23	140	21,1
UR7016240102TAT	420/70 R24 (14.9 R24)	TL	16,5	49,1	130/130	A8/B	55	R-1W	4180	23	146,5	22
UR7016240102TAT	460/70 R24	TL	18,1	49,6	152/149	A8/B	43	R-1W	7850	46	147,8	22,2
UR7016240102TAT	360/70 R28 (12.4 R28)	TL	14,1	49,4	125/125	A8/B	48	R-1W	3640	23	148,5	22,6
UR7016240102TAT	380/70 R28 (13.6 R28)	TL	14,5	50,9	127/127	A8/B	53	R-1W	3860	23	152,7	23,1
UR7016240102TAT	420/70 R28 (14.9 R28)	TL	16,5	51,2	133/133	A8/B	55	R-1W	4540	23	159,2	24

POWER-X

Radial Tractor Tire

TATKO

AG





POWER-X

Radial Tractor Tire

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
85 SERIES												
UR8520280102TAT	280/85 R20 (11.2 R20)	TL	11,1	38,7	112/109	A8/B	38	R-1W	2470	23	115,8	17,5
UR8520320102TAT	320/85 R20 (12.4 R20)	TL	12,6	41,4	119/116	A8/B	40	R-1W	3000	23	123,4	18,6
UR8524250102TAT	250/85 R24	TL	9,9	40,8	109/109	A8/B	42	R-1W	2270	23	122,9	18,7
UR8524280102TAT	280/85 R24 (11.2 R24)	TL	11,1	42,8	115/112	A8/B	44	R-1W	2680	23	128,4	19,5
UR8524320102TAT	320/85 R24 (12.4 R24)	TL	12,6	45,4	122/119	A8/B	44	R-1W	3300	23	136	20,6
UR8524340102TAT	340/85 R24 (13.6 R24)	TL	13,5	46,8	125/122	A8/B	50	R-1W	3640	23	139,8	21,1
UR8524380102TAT	380/85 R24 (14.9 R24)	TL	14,7	49,4	131/128	A8/B	58	R-1W	4300	23	147,4	22,2
UR8528280102TAT	280/85 R28 (11.2 R28)	TL	11,1	46,7	118/115	A8/B	44	R-1W	2910	23	140,9	21,5
UR8528320102TAT	320/85 R28 (12.4 R28)	TL	12,6	49,4	124/121	A8/B	47	R-1W	3520	23	148,5	22,6
UR8528340102TAT	340/85 R28 (13.6 R28)	TL	13,5	50,7	127/124	A8/B	48	R-1W	3860	23	152,2	23,1
UR8528380102TAT	380/85 R28 (14.9 R28)	TL	15	53,4	133/130	A8/B	52	R-1W	4540	23	159,8	24,1
UR8528420102TAT	420/85 R28 (16.9 R28)	TL	16,5	56,1	139/136	A8/B	53	R-1W	5360	23	167,4	25,2
UR8530380102TAT	380/85 R30 (14.9 R30)	TL	15	55,4	135/132	A8/B	52	R-1W	4800	23	166,1	25,1
UR8530420102TAT	420/85 R30 (16.9 R30)	TL	16,5	58,1	140/137	A8/B	55	R-1W	5520	23	173,7	26,3
UR8530460102TAT	460/85 R30 (18.4 R30)	TL	17,9	60,8	145/142	A8/B	60	R-1W	6400	23	181,2	27,3
UR8534420102TAT	420/85 R34 (16.9 R34)	TL	16,5	62,1	142/139	A8/B	55	R-1W	5840	23	186,3	28,3
UR8534460102TAT	460/85 R34 (18.4 R34)	TL	17,9	64,8	147/144	A8/B	60	R-1W	6800	23	193,9	29,3
UR8536340102TAT	340/85 R36 (13.6 R36)	TL	13,5	58,9	132/129	A8/B	49	R-1W	4400	23	177,7	27,1
UR8538340102TAT	340/85 R38 (13.6 R38)	TL	13,5	60,8	133/130	A8/B	49	R-1W	4540	23	183,9	28,1
UR8538380102TAT	380/85 R38 (14.9 R38)	TL	15	63,4	139/136	A8/B	50	R-1W	5360	23	191,3	29,1
UR8538420102TAT	420/85 R38 (16.9 R38)	TL	18,9	52,6	142/145	D/A8	55	R-1W	5840	35	157,6	23,9
UR8538460102TAT	460/85 R38 (18.4 R38)	TL	17,9	68,8	149/146	A8/B	60	R-1W	7150	23	206,4	31,3
UR8538520102TAT	520/85 R38 REINFORCED	TL	20,3	72,8	155/152	A8/B	64	R-1W	8550	23	217,8	32,9
95 SERIES												
UR9532230102TAT	230/95 R32 (9.5 X 32)	TL	9,1	49,4	128/128	A8/B	37	R-1W	3960	58	149,8	23
UR9548230102TAT	230/95 R48	TL	9,1	65,3	136/136	A8/B	42	R-1W	4940	58	199,9	30,9

FARM-R

Bias Rear Tractor Tire

- ✔ Offers high traction
- ✔ Specially designed to avoid the accumulation of mud and soil while in motion
- ✔ It features windowed blocks that facilitate the release of mud, making it easier to clean

TATKO



FARM-R

Bias Rear Tractor Tire

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
FARM-R												
U5242021TAT	9.50-24 8PR	TT	9,5	41,3	116	A6	35	R-1	2760	34	124,4	18,9
U5243021TAT	11.2/10-24 8PR	TT	11,2	43,5	116	A6	40	R-1	2760	34	130,6	19,8
U524402TAT	12.4/11-24 8PR	TT	12,4	45,7	118	A6	40	R-1	2910	29	136,7	20,7
U5282021TAT	12.4/11-28 8PR	TT	12,4	49,6	124	A6	39	R-1	3640	30	149	22,6
U5361021TAT	12.4/11-36 8PR	TT	12,4	57,7	128	A6	40	R-1	3740	29	174,4	26,7
U5283021TAT	13.6/12-28 8PR	TT	13,6	51,6	125	A6	42	R-1	3640	29	154,6	23,4
U5362021TAT	13.6/12-36 8PR	TT	13,6	59,6	125	A6	40	R-1	4080	29	180	27,4
U5246021TAT	14.9/13-24 8PR	TT	14,9	49,8	130	A6	40	R-1	3960	26	148,3	22,3
U5284021TAT	14.9/13-28 8PR	TT	14,9	53,7	136	A6	39	R-1	4180	26	160,7	24,3
U5302021TAT	16.9/14-30 8PR	TT	16,9	58,5	137	A6	44	R-1	5080	25	174,7	26,4
U5303021TAT	18.4/15-30 8PR	TT	18,4	61	144	A6	43	R-1	5360	20	182	27,4
U5301031TAT	14.9/13-30 10PR	TT	14,9	55,7	139	A6	43	R-1	4940	29	166,9	25,3
U5302031TAT	16.9/14-30 10PR	TT	16,9	58,5	142	A6	44	R-1	6150	28	174,7	26,4
U5341031TAT	16.9/14-34 10PR	TT	16,9	62,4	126	A6	43	R-1	5840	29	187,1	28,3
U5244041TAT	12.4/11-24 12PR	TT	12,4	45,7	129	A6	40	R-1	3520	35	136,7	20,7
U5303261TAT	18.4/15-30 16PR	TT	18,4	61	158	A6	43	R-1	9350	45	182	27,4

FARM-F

Bias Front Tractor Tire

- ✔ Offers comfortable and safe ride
- ✔ Comes with deeper treads to enhance its puncture resistance
- ✔ Equipped with clean out features

TATKO



AG

FARM-F

Bias Front Tractor Tire



Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
FARM-F												
U3162111TAT	6.00-16 6PR	TT	6,5	6,5	88	A6	15	F-2	1230	48	86,9	13,2
U3191011TAT	6.00-19 6PR	TT	6,9	6,5	93	A6	15	F-2	1430	48	96,6	14,7
U3164211TAT	7.50-16 6PR	TT	8,1	8,1	98	A6	15	F-2	1650	41	94,6	14,3
U3163121TAT	6.50-16 8PR	TT	8,1	6,9	97	A6	15	F-2	1610	54	89,6	13,6
U3164211TAT	7.50-16 8PR	TT	6,5	8,1	103	A6	15	F-2	1930	54	94,6	14,3



FLOT-141

Bias Flotation Tires

TATKO

- ✔ Constructed with extra-strong casing
- ✔ Equipped with deep tread profile



AGRO

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
			FLOT-141									
U4153672TAT	400/60-15.5 18PR	TL	15,9	34,4	151	A8	24	I-3	7600	90	102,2	15,3

IMP-111

Bias Flotation Tires

TATKO

- ✔ Offers high load carrying capacity
- ✔ Well designed tread pattern to reduce rolling resistance
- ✔ Provided with wide footprint for great flotation



AGRO

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
IMP-111												
U4151042TAT	10.0/75-15.3 12PR	TL	10,4	29,9	126	A8	15	I-1	3740	68	89,4	13,5
U4152052TAT	11.5/80-15.3 14PR	TL	11,4	33,3	139	A8	15	I-1	5360	69	68,9	14,8
U4153152TAT	12.5/80-15.3 14PR	TL	12,1	35	142	A8	15	I-1	5840	62	103,8	15,5

RMK-121

Bias Flotation Tires

TATKO

- ✔ Provided with a multi-purpose tread pattern for usage on hard surfaces and soil
- ✔ Offered with durable side wall
- ✔ Equipped with grooves for traction and angled shoulders



AGRO

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
			RMK-121									
U4161141TAT	7.50-16 12PR	TT	8,4	31	121	A8	19	-	3200	72	92,6	14

RMK-131

Bias Flotation Tires

TATKO

- ✔ Strong casing construction for greater resistance
- ✔ Guarantees excellent performance in soil and on hard surface conditions
- ✔ Equipped with mud-repellent and enhanced traction features



AGRO

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
			RMK-131									
U4162041TAT	9.00-16 12PR	TT	9,7	34,1	125	A6	25	-	3640	58	101,3	15,2

AGRO



AGRO





INDUSTRIAL

INDUSTRIAL



SK-165

Bias EM/Industrial Tires

- ✔ Its flexible sidewall structure, provides a comfortable drive
- ✔ Specially designed for challenging conditions
- ✔ Offers excellent maneuverability thanks to its reinforced shoulder blocks

TATKO



INDUS-
TRIAL

SK-165

Bias EM/Industrial Tires



Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
SK-165												
U6161142TAT	10-16.5 12PR	TL	11,1	30,5	138	A3	38	L4	5200	84	91,5	13,9
U6162152TAT	12-16.5 14PR	TL	12,6	33,3	148	A3	42	L4	6950	90	99,4	15



CST-27

Bias EM/Industrial Tires

- ✔ Possesses excellent selfcleaning capabilities and high traction because to its deep and corrugated tread structures.
- ✔ Strong center-bar structure, offers greater wear and puncture resistance
- ✔ Provides impact resistant tread compounds and guarantees durability with its resistance to stone cuts, cracks, and break

INDUS-
TRIAL

TATKO



CST-27

Bias EM/Industrial Tires

Product Code	Tire Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Tread Depth 32nds	TRA Code	Load & Pressure			
			Section Width in	Overall Diameter in					Tire Load Capacity lbs	Tire Pressure At Max. Load Psi	Dynamic Rolling Circumference in	Static Loaded Radius in
CST-27												
U6182152TAT	12.5/80-18 14PR	TL	11,2	37,6	146	A8	30	R-4	6600	62	112	16,9
U6281052TAT	16.9/14-28 14PR	TL	16,9	55,5	156	A8	32	R-4	8800	43	165,7	25
U6261052TAT	18.4/15-26 14PR	TL	18,4	56,1	160	A8	32	R-4	9900	42	166,8	25
U6243062TAT	15.5/80-24 16PR	TL	16,2	50	162	A8	40	R-4	10500	72	148,8	22,4
U6207062TAT	16.0/70-20 16PR	TL	15,2	43	166	A2	33	R-4	11700	65	127,7	19,2
U6246062TAT	16.9-24 16PR	TL	16,9	51,6	154	A8	34	R-4	8250	46	153,3	23





OFF-THE-ROAD

OFF-THE-ROAD



Hi-Traction Grader Off-The-Road Tires

TATKO

✔ Provides superior traction with its specially designed tread pattern

✔ Long-lasting thanks to the improved tread compound

✔ Resistant to impacts with its strong carcass structure

OFF-THE-
ROAD



Hi-Traction Grader

Off-The-Road Tires



Product Code	Tire Size	TT/TL	Inflated Unloaded		Load Index	Speed Symbol	Load & Pressure			
			Section Width	Overall Diameter			Tire Load Capacity	Tire Pressure At Max. Load	Dynamic Rolling Circumference	Static Loaded Radius
mm	mm	kg	Psi	mm	mm					
HI-TRACTION GRADER										
U6242062TAT	14.00-24 16PR	TL (16 PLY)	375	1320	153	A8	3650	375 KPA (54 Psi)	4144,8	600





Merdivenköy Mh. Nur Sk. A Blok No: 1/1 İç Kapı No:141
34732 Kadıköy, İSTANBUL
Tel: +90 850 222 0 136 | E-Mail: info@tatkolastik.com
www.tatkolastik.com